



# DYNEEMA® D-ROPE DUPLEX



## DUPLEX SK75

spec. gravity: 0.97  
 melting point: 150 °C  
 max. elongation: 4 %

**D-Rope DUPLEX**  
 for heavy duty applications:

**improved resistance against  
 abrasion,  
 buckling  
 and torsion**

will ensure a longer lifetime.

DUPLEX is designed as an alternative  
 to overbraided D-Rope,  
 when easy handling  
 and quick repairs are required.

| Diam<br>[mm] | Weight<br>[kg/100m] | Av. Breakload<br>[t] |
|--------------|---------------------|----------------------|
| 8            | 3,8                 | 4,9                  |
| 10           | 6,0                 | 7,5                  |
| 12           | 8,4                 | 11,0                 |
| 14           | 11,6                | 14,5                 |
| 16           | 14,7                | 18,5                 |
| 18           | 18,9                | 23,8                 |
| 20           | 23,1                | 29,0                 |
| 22           | 27,3                | 35,7                 |
| 24           | 32,6                | 40,8                 |
| 26           | 37,8                | 49,3                 |
| 28           | 44,1                | 57,8                 |
| 30           | 50,4                | 66,3                 |
| 32           | 57,8                | 75,7                 |
| 34           | 65,1                | 85,0                 |
| 36           | 72,5                | 94,4                 |
| 38           | 80,9                | 104,6                |
| 40           | 90,3                | 115,6                |
| 42           | 98,7                | 125,8                |
| 44           | 109,2               | 142,8                |
| 46           | 118,7               | 154,7                |
| 48           | 129,2               | 165,8                |

Dyneema® D-Rope is available in:  
 SK62, SK75 (XBO), SK78 (XBO), SK90, HS and DUPLEX.