



DYNEEMA® D-ROPE SK62 and SK75

12 strand plaited



SK62
SK75

spec. gravity: 0.97
melting point: 150 °C
max. elongation: 4 %

Diam [mm]	Circumf. [inch]	Weight [kg/100m]	Av. Breakload [t]	Av. Breakload [t]
4	0.50	0.9	1.1	1.4
5	0.63	1.5	1.6	2.2
6	0.75	2.0	2.4	3.2
7	0.88	2.7	3.3	4.6
8	1.00	3.6	4.6	5.8
9	1.13	4.7	7.2	7.3
10	1.25	5.7	8.6	9.1
12	1.50	8	10	13
14	1.75	11	14	17
16	2.00	14	18	22
18	2.25	18	22	28
20	2.50	22	27	34
22	2.75	26	33	42
24	3.00	31	39	48
26	3.25	36	47	58
28	3.50	42	54	68
30	3.75	48	62	78
32	4.00	55	71	89
34	4.25	62	80	100
36	4.50	69	89	111
38	4.75	77	98	123
40	5.00	86	108	136
42	5.25	94	120	148
44	5.50	104	132	168
46	5.75	113	144	182
48	6.00	123	156	195
50	6.25	138	168	203
52	6.50	150	180	215



Dyneema® D-Rope is available in SK62 SK75 (XBO) SK78 (XBO) SK90, HS and DUPLEX. All D-Rope can be supplied with different types of overbraid, such as Dyneema®, polyester or customised solutions.