

HAWKLINE

HAWKLINE: a competitive 12 strand rope made from high quality 'T70' HMPE, produced by DSM. The ropes are manufactured to high standard in our factory in The Netherlands. We can supply quickly, often from stock. Our splicers are ready to construct slings and roundslings.

- HAWKLINE is 12 strand braided as per ISO 10325
- Breaking load wet and dry is equal.
- Breaking load of spliced rope is minus 10% as per ISO 2307
- Spec. gravity 0.97
- Melting Temperature 150 °C
- Max. elongation 4%

Standard coating is in Gold or Grey Powercoat.

Diam (mm)	Circumf. (inch)	Weight (kg/100m)	Min. Breakload (t)
2	0.25	0.4	0.7
3	0.37	0.5	0.9
4	0.50	1.1	1.4
5	0.63	1.5	2.2
6	0.75	2.0	3.7
7	0.88	2.7	4.6
8	1.00	3.6	6.0
10	1.25	5.9	10.4
12	1.50	8	14
14	1.75	11	18
16	2.00	14	24
18	2.25	18	30
20	2.50	22	38
22	2.75	27	45
24	3.00	33	53
26	3.25	37	61
28	3.50	43	69
30	3.75	48	78
32	4.00	55	89
34	4.25	62	100

Diam (mm)	Circumf. (inch)	Weight (kg/100m)	Min. Breakload (t)
36	4.50	69	110
38	4.75	77	121
40	5.00	86	134
42	5.25	98	145
44	5.50	104	160
46	5.75	115	174
48	6.00	126	190
50	6.25	136	203
52	6.50	146	215
56	7.00	172	250
60	7.50	196	280
64	8.00	220	314
68	8.50	248	348
72	9.00	290	380
80	10.0	357	459
88	11.0	425	530
96	12.0	506	630
104	13.0	595	685
112	14.0	695	790
120	15.0	793	902

HAWKLINE can be supplied with a protective jacket. This overbraid can be made from ht polyester or HMPE.

