

HAWKLINE PRO

HAWKLINE with jacket: a rope suitable for use where abrasion is expected.

The core is 12 strand braided, made from T70 (HMPE). The firm protective jacket is made from high tenacity polyester.

- Core: 12 strand braided as per ISO 10325
- Breaking load wet and dry is equal.
- Breaking load of spliced rope is minus 10% as per ISO 2307

Standard coating of the 12 strand core is in Gold Powercoat.

Diam. core (mm)	Diam. fin. (mm)	Circumf. (inch)	Weight (kg/100m)	Min. Breakload (t)
16	20	2.5	27	24
18	22	2.75	33	30
20	24	3.00	40	38
22	26	3.25	49	45
24	28	3.50	59	53
26	30	3.75	67	61
28	32	4.00	77	69
30	34	4.25	86	78
32	36	4.50	99	89
34	38	4.75	105	100
36	41	5.15	110	110
38	43	5.40	123	121
40	46	5.75	138	134
42	48	6.00	157	145
44	50	6.25	166	160
46	52	6.50	184	174
48	54	6.75	202	190
50	56	7.00	218	203
56	62	7.75	275	250
60	66	8.25	310	280

- Spec. gravity 1.06
- Melting Temperature core 150 °C
- Melting Temperature jacket 265 °C

- Standard colour jacket: white
- Water absorption 0%
- Max. elongation 4%

HAWKLINE PRO can be supplied with soft or hard (thimble) eyes. Depending on the application we will recommend a type of protection over the eye and splice:

- hollow braided cover
- mechanically braided splice cover
- shrink hose
- fire hose
- resin

HAWKLINE PRO is available in a range from 4 mm up to 104 mm.

HAWKLINE PRO has a polyester jacket as a standard.

Other options for jacket material:

- T70 (HMPE)
- Polyester/T70 (HMPE)
- Polyester/Technora®
- custom solutions

